

Shenandoah

☞ SPECIFICATIONS

Style Number:	SHE40204
Plank Size:	7.17" x 48.03"
Overall Thickness:	5.0 mm
Product Construction:	4.0 mm SPC + 1.0 mm MaxStepPro™
Wear Layer:	20 mil with MaxProtect®
Edge:	ColorEdge™
Gloss Level:	Matte
Installation Method:	i4F Triple-Lock® Click4U®
Recycled Content:	None
Certifications:	GreenGuard Gold®

Classification	ASTM F3261-20	Class I, Type B, Grade 2, Backing Class B
Chemical Resistance	ASTM F 925	Passes
Critical Radiant Flux	ASTM E 648-06	Passes
Dimensional Stability	ASTM F 2199	Passes
Residual Indentation	ASTM F 1914	Passes
Resistance to Heat	ASTM F 1514	Passes
Resistance to Light	ASTM F 1515	Passes
Smoke Density	ASTM E 662	Passes
Thickness w/ Foam Layer	ASTM F 387	5.0 mm
Thickness, Wearlayer	ASTM F410	.3 mm
Size Tolerance	ASTM F2055	Passes
Flatness	ISO 24337	Passes
Openings	ISO 24337	Passes
Ledging	ISO 24337	Passes
Static Load	ASTM F970	Passes

☞ PACKAGING

Square Feet Per Carton:	23.90	Pieces Per Carton:	10
Square Feet Per Pallet:	1,553.50	Cartons Per Pallet:	65
Square Feet Per Container:	31,070	Pallets Per Container:	20
Weight Per Carton:	34.72 lbs	Weight Per Pallet:	2,256.80 lbs

☞ COLOR LINE

5001 Alder	5054 Cortland
5002 Bingham	5056 Dryfork

☞ WARRANTIES

Lifetime Limited Waterproof*	20 Year Limited Residential Wear*	5 Year Light Commercial Wear*
------------------------------	-----------------------------------	-------------------------------

*Please visit our website for full warranty details.